



The Professional Choice For Security

3 Year HotSwap Warranty



Features

- 600 x 300dpi crisp, clear resin printing
- Custom Holokote Security Water Mark
- Secure Digital Ribbon Shredding
- Fast 190 Cards Per Hour
- WiFi Standard
- 3 Year HotSwap Warranty
- Windows | Mac OS X | Linux *see specs
- Optional: MIFARE®, DESFire® and iClass®


Ideal For

High-Security Environments:

- Education Providers
- Government Departments
- Clubs and Associations
- Registered Training Organisations
- Healthcare
- Secure Facilities

























LD 4000SPECIFICATIONS AT A GLANCE

B	 CBECI		
	V 10 10 1		
		FICATI	

one area of the HoloKote watermark is highlighted as a high visibility security seal. A ch HoloKote designs which can be changed to be 10 custom designs. For added security, Cenables customisation of the watermark to an individual logo or security design Once data has been used for the print job, it is fragmented, rendering it irrecoverable, it	oice of 10 standard		
I DIGITAL INTENDING	A HoloKote security watermark can be printed across the card surface. When used with HoloPatch cards, one area of the HoloKote watermark is highlighted as a high visibility security seal. A choice of 10 standard HoloKote designs which can be changed to be 10 custom designs. For added security, Custom HoloKote enables customisation of the watermark to an individual logo or security design		
PPC ID4000 is not a repository for data	Once data has been used for the print job, it is fragmented, rendering it irrecoverable, helping to ensure the PPC ID4000 is not a repository for data		
Warranty 3 year Max Cover Plus warranty, which includes printhead warranty and free HotSwap	service		
Printer Interfaces High Speed USB 2.0, USB 3.0 compatible – Type B, 10/100 Ethernet, Wi-Fi			
Software Drivers Win XP, Vista, 7, 8, 10 (32 & 64) Win server 2003 R2 SP2, 2008-16. Mac OS X 10.9.0+. Linu	Win XP, Vista, 7, 8, 10 (32 & 64) Win server 2003 R2 SP2, 2008-16. Mac OS X 10.9.0+. Linux with CUPS support.		
Card Capacity 100 card Input Hopper, 70 card Output Hopper			
Weight 4.7kg			
Power Source External power supply 100-240V 50-60Hz autoranging			
Dimensions 475.5mm L x 211.5mm W x 248mm H including Feeder and Stacker			
Environment Sheltered office environment 10°C to 30°C			
Print Speed Colour: 190 cards/hr & Monochrome: 720 cards/hr (single-sided card)			

NSU		

Dye Film	ID4000 Printers require the use of High Performance ID4000 Series ribbons for full colour 600dpi printing
Card Types	All standard PVC ISO CR80 & CR79 sized cards HoloPatch cards are available. Works with HoloKote to produce a highly-visible gold seal on the card
Card Thickness	0.51mm to 1.03mm

_	_	
\mathbf{n}		NIC
-		

01 110110	
Custom HoloKote Kit	HoloKote Flex or HoloKote available.
Dual-Sided Upgrade	Upgrade the ID4000 to the ID4000Duo
Magstripe Encoder	Optional ISO 7911 Magnetic Stripe Encoder (Factory Fitted)
Contactless Card Encoder	Contactless cards supported : NXP MIFARE [®] , DESFire [®] , Genuine 125kHz Prox & more upon request

W	ΑF	474	ΛΛ	lΤ	ς
	AU	ш	444		J

ID4000	PPC ID4000 single-sided ID Card Printer		
ID4000 Duo	PPC ID4000 dual-sided ID Card Printer		
Mag/Chin	PPC ID4000 ID Card Printer with Magnetic Stripe Encoder and Smart Card Encoder		
Mag/Chip	MIFARE, DESFire, Genuine 125kH Prox & contact chip, combi (other smart card encoders also available)		

The ID4000's superior card printing quality is complemented with a full range of options: single or double sided printing, secure encoding with mag and contactless technology and the built in HoloKote can be customised to an individual logo or security design.



Card Printers, it's what we do.

BRISBANE | SYDNEY | MELBOURNE



www.ppc.com.au1300 651 277