

ID 350

Powered by  ZEBRA

PPC[®]
ID Card Solutions 



Ideal For

Instant Issuance:

- Clubs and Associations
- Retail and Hospitality
- Employee ID
- Student ID

Features

- 300 dpi print resolution
- Full range of encoding options
- Automatic adjustment to card thickness
- High-Volume card printing
- Flexibility for batch printing or one-off hand-feed printing
- 3 Year Warranty



Edge to edge



Duplex upgrade



Ethernet



Magnetic stripe



Smart card encoding



3 Year Warranty



Hand Feed Override

ID350

SPECIFICATIONS AT A GLANCE

PRINTER SPECIFICATIONS

Warranty	36 Months Return to Base
Printer Interfaces	USB 2.0 compatible and Ethernet both fitted as standard
Software Drivers	Windows 2003, 2008, 2012, Win-7, 8/8 Pro and Windows 10, 11, Linux Ubuntu and Apple iOS 10.2 drivers all supplied with printer
Card Capacity	100 card Input Hopper and 100 card Output Hopper
Weight	4kg Simplex & 4.4kg Duplex
Power Source	Auto-switching single-phase AC power 90-132VAC and 190-264VAC RMS and 47-63Hz FCC Class A
Dimensions	258mm L x 157mm W x 383mm H (Simplex) & 258mm L x 157mm W x 468mm H (Duplex)
Environment	Sheltered office environment 15°C to 35°C
Print Speed	Colour: 200 cards per hour (single-sided) & Monochrome: 900 cards per hour (single-sided)

CONSUMABLES

Card Types	All standard PVC ISO CR80 sized cards
Card Thickness	0.25mm to 1.0mm

OPTIONS

Magstrip Encoder	Optional ISO 7811 Magnetic Stripe Encoder
-------------------------	---

VARIANTS

ID350	ID350 single-sided ID Card Printer
ID350 Duo	ID350 dual-sided ID Card Printer
ID350 Mag	ID350 ID Card Printer with Magnetic Stripe Encode

The ID350 is an ideal solution for low- to medium-volume printing applications that require minimal operator training and excellent print quality while offering advanced features and high capacity media options.



Card Printers, it's what we do.

BRISBANE | SYDNEY | MELBOURNE



Proudly 100% Australian
Owned & Operated

Specifications subject to change E & OE

 www.ppc.com.au

 **1300 651 277**

ABN: 51 433 835 994